



SecurityServer Se Gen2

CryptoServer
The Root of Trust HSM




Utimaco SecurityServer Se-Series Gen2 –
The general purpose Hardware Security Module

Key Features

The SecurityServer Se Gen2 from Utimaco ensures the security of cryptographic key material for servers and applications. It includes integration software that supports the industry standard PKCS#11, Microsoft CSP/CNG/SQLEKM and JCE interfaces.

It can therefore be used for numerous applications, including e.g. public key infrastructures (PKIs), database encryption. The SecurityServer Se Gen2 is available as a PCIe plug-in card or as network-attached appliance.





Product Highlights

Low operational costs

- Highest performance at an attractive price
- Inexpensive starter models for applications with low performance requirements
- Extensive remote administration
- Efficient key management and firmware updates via remote access
- Automation of remote diagnosis via SNMP (Simple Network Management Protocol)
- Software simulator for evaluation and integration testing



HSM Functionalities

Features

- Secure key storage and processing
- Extensive key management
- Secure key storage inside HSM or as external encrypted key files
- 2-factor authentication with smartcards
- "m out of n" authentication (e.g. 3 out of 5)
- Configurable role-based access control and separation of functions
- Multi-tenancy support
- Remote management
- Software simulator for evaluation and integration testing
- Supported operating systems: Windows and Linux
- Multiple integrations with PKI applications, database encryption, etc.
- All features included in product price



Cryptographic algorithms


- RSA, DSA, ECDSA with NIST and Brainpool curves
- DH, ECDH with NIST and Brainpool curves
- AES, Triple-DES, DES
- MAC, CMAC, HMAC
- SHA-1, SHA2-Family, SHA3, RIPEMD
- Hash-based deterministic random number generator (DRG.4 acc. AIS 31)
- True random number generator (PTG.2 acc. AIS 31)
- Up to 10,000 RSA or 6,000 ECDSA signing operations in bulk processing mode
- All algorithms included in product price

Application programming interfaces (APIs)

- PKCS#11
- Java Cryptography Extension (JCE)
- Microsoft Crypto API (CSP), Cryptography Next Generation (CNG) and SQL Extensible Key Management (SQLEKM)
- Cryptographic eXtended services Interface (CXI) – Utimaco's high performance interface ensures easy integration of cryptographic functionality into client applications



Technical specifications PCIe card



Physical Dimensions

- **Form factor:** Half-length, full-height single lane PCI Express card
- **Compatibility:** PCIe 1.1, PCIe 2.0 and PCIe 3.0 slots
- **Height:** 111.15 mm ("full" height)
- **Weight:** 400 g



Connectivity

- **Interface:** USB



Electrical

- **Power Supply:** 3 V lithium battery, Ø 12 mm, length 600 mm, FDK CR 12600 SE or VARTA CR2NP
- **Operating voltage:** 3.3 V



Operating Environment

- **Operating temperature:** +10°C to +45°C (+50°F to +113°F)
- **Storage temperature:** -10°C to +55°C (+14°F to +131°F)
- **Relative humidity:** 10% to 95%, non-condensing
- **MTBF:** 360,000 hours at 25°C / 77°F



Certification/Compliance

- **Safety:** FIPS 140-2 Level 3, UL, IEC/EN 60950-1, CB certificate
- **Emissions:** CE, FCC Class B
- **Environmental:** RoHS II, WEEE



Technical specifications Network appliance



Physical Dimensions

- **Form factor:** 19" 1U
- **Width:** 446 mm excluding brackets
- **Depth:** 533.4 mm excluding handles
- **Height:** 44 mm
- **Weight:** 10 kg



Connectivity

- **Interfaces:** 2 RJ45, 1 Gb/s



Electrical

- **Power Supply:** Redundant field-replaceable power supply: 2 x 100 ~ 240 V AC, 50 ~ 60 Hertz, 300 W
- **Power consumption:** typically 45 W / 66 VA, max. 50 W / 70 VA
- **Heat dissipation:** max. 171 BTU/h



Operating Environment

- **Operating temperature:** +10°C to +50°C (+50°F to +122°F)
- **Storage temperature:** -10°C to +55°C (+14°F to +131°F)
- **Relative humidity:** 10% to 95%, non-condensing
- **MTBF:** 100,000 hours at 25°C / 77°F, environment GB, GC – Ground Benign, Controlled



Certification/Compliance


- **Safety:** FIPS 140-2 Level 3, UL, IEC/EN 60950-1, CB certificate
- **Emissions:** CE, FCC Class B
- **Environmental:** RoHS II, WEEE





EMEA

Utimaco IS GmbH


 Germanusstraße 4
52080 Aachen,
Germany

 +49 241 1696 200

 hsm@utimaco.com

Americas

Utimaco Inc.


 900 E Hamilton Ave.,
Suite 400
Campbell, CA 95008,
USA


 +1 844 UTIMACO


 hsm@utimaco.com

APAC

Utimaco IS Pte Limited

 80 Raffles Place,
#32-01, UOB Plaza
Singapore 048624

 +65 6622 5347

 hsm@utimaco.com

For more information about Utimaco HSM products, please visit:

hsm.utimaco.com

© Utimaco IS GmbH 09/19

Utimaco® is a trademark of Utimaco GmbH. All other named Trademarks are Trademarks of the particular copyright holder. All rights reserved. Specifications are subject to change without notice.